

AC-Q41H

Anti-Vandal PIN Standalone Controller



THIS ADVANCED 500-USER STANDALONE CONTROLLER FEATURES ANTI-VANDAL METAL KEYS FOR PIN CODE USER CREDENTIALS. AC-Q41H HAS A RUGGED METAL BODY IDEAL FOR INSTALLATION IN HIGH TRAFFIC ENVIRONMENTS. THIS MODEL COMES WITH REMOVABLE TERMINAL BLOCKS, ALLOWING QUICK INSTALLATION, AND UTILIZES ADVANCED PROGRAMMING OPTIONS.

GENERAL DESCRIPTION

The AC-Q41H anti-vandal controller has a unique combination of metal keys and built-in heater, offering a higher level of user accessibility in low light and temperatures.

AC-Q41H has an attractive profile, free from sharp edges, ideal for installations where style and functionality are highly important.

This feature-rich unit offers all weather operation, with flexible programming capabilities including a unique "code search" for simple user management.

Non-volatile memory protects the storage of user database, modes and parameters.

MAIN FEATURES

- 500 PIN users
- Smooth attractive design, with anti-vandal body
- 3 operational security levels can be selected with special PIN codes
- Supports up to 8-digit PIN codes, with timed wrong code lockout after several wrong attempts

- 2 tri-colored LEDs and integral sounder for programming and operational indications
- Removable terminal blocks for unit wiring

PROFESSIONAL GRADE FEATURES

- Optical tamper detection
- Automatic internal heater prevents key freeze at -20°C (4°F).
- 10 programmable modes for auxiliary input and output (2 Amp Form C Relay)
- 2 Amp Form C Lock Strike Relay, for fail-safe and fail-secure, with input for REX
- Supports: Door Ajar, Forced, Shunt, Monitor, and Secure mode
- Door bell key feature operation (from '*' key), with Rosslare's BL-D40 accessory
- Wide range of low voltage AC/DC power input

SPECIFICATIONS

ELECTRICAL SPECIFICATIONS

■ Operating Voltage Range	12 to 24 VDC, from a regulated power supply 16 to 24 VAC, from a transformer
■ Input Current	(Heater Off) Standby: 40 mA, Maximum: 100 mA, at 12 VDC (Heater On) Standby: 520 mA, Maximum: 580 mA, at 12 VDC
■ Relay Outputs	Lock Strike: 2A, N.O. and N.C. Auxiliary: 2A, N.O. and N.C.
■ Tamper	Optical back tamper sensor, O.C. active low 32 mA max sink current
■ Inputs	REX: N.O. Dry Contact Auxiliary (In/Monitor): N.O. Dry Contact, 10 programmable modes

OPERATIONAL SPECIFICATIONS

■ Capacity	500 users, single/dual code each
■ Keypad	3x4 keys for local programming and 4- to 8-digit PIN codes entry
■ User Levels	Normal, Secure, Master
■ Security Modes	Normal, Bypass, Secure
■ Audio/Visual	Interface for BL-D40 (bell, chime, and siren enunciator) Two tri-color LED indicators, built-in sounder
■ Design	Rugged metal enclosure, highly strong construction, metallic keys. Suitable for extremely harsh environments.

ENVIRONMENTAL SPECIFICATIONS

■ Operating Environment	Water resistant, suitable for outdoor use, IP54 rated
■ Operating Temperature	-20°C to 60°C (-4°F to 140°F). Built-in heater to prevent key freezing
■ Operating Humidity	0 to 95% (non-condensing)
■ RFI Protection	> 20 V/m up to 1000 MHz

PHYSICAL SPECIFICATIONS

■ Dimensions (L x W x H)	120 x 76 x 27 mm (4.72 x 3 x 1.06 in.)
■ Weight	440 g (1 lbs)

SYSTEM COMPONENTS

The AC-Q41H is compatible with the BL-D40 alarm, chime and door bell enunciator/strobe unit, as well as with the EX-01 Push to Exit button.

PRODUCT WARRANTY

5-year Limited Product Warranty

ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS).

Visit our website: www.rosslaresecurity.com



ROSSLARE
SECURITY PRODUCTS
Experience The Difference