

AY-Q54

Anti Vandal 3x4 PIN Reader

The AY-Q54 has a slim rugged metal construction ideal for high traffic and harsh environments where PIN code credentials are needed. This model is epoxy filled, designed to withstand the rigors of the outdoor environment, and has advanced programming options. This elegant yet robust model can be easily interfaced with Rosslare's or most third-party controllers.

General Description

For greater peace of mind, this sturdy access control unit provides a rugged reader with advanced access control features, in an aesthetically-designed housing.

The AY-Q54 offers programmable PIN transmission formats, LED Control, and tamper detection, in order to provide extra security and flexibility.

Come rain or shine, this reader can handle the challenge, with its rugged metal housing and waterproof enclosure for maximum durability.

The unit has an attractive slim profile, free from sharp edges, ideal for installations where style and rigidity are important.



Main Features

- Supports 4-Digit to 8-Digit PIN credentials.
- Smooth, attractive design, with all-weather indoor and outdoor operation.
- Large, metallic Keypad.
- 2 tri-colored LEDs and an integral sounder for programming and operation.
- User friendly menu system based on keypad, LED and sounder indicators.
- Back Optical tamper detection output.
- Door bell feature ('*' key), when operated with Rosslare controllers.

PROFESSIONAL GRADE FEATURES

- 8 Selectable PIN transmission modes including options for Key stream, Binary, Parity, and 3x4 Matrix.
- Selectable Wiegand or Clock & Data output formats.
- Programmable facility code.
- Comes with a mounting and drilling label, security screw, and tool set to prevent unauthorized opening.
- 60 cm (23.6 in.) shielded interface cable.

AY-Q54 Anti Vandal 3x4 PIN Reader



Product Specifications

| | |
|--------------------------------------|--|
| ELECTRICAL CHARACTERISTICS | |
| • Operating Voltage Range: | 5-16 VDC, from a regulated power supply. |
| • Input Current: | Standby: 30mA at 12 VDC Maximum: 70mA at 12 VDC |
| • LED Control: | Dry Contact, N.O. |
| • Tamper: | Optical back tamper sensor, O.C. active low 32mA max sink current |
| OPERATIONAL CHARACTERISTICS | |
| • Keypad: | 3x4 Keys for PIN codes entry and local programming Door bell key ('*') function (with Rosslare controllers only) |
| • Facility code: | Programmable |
| • PIN Code formats: | 8 selectable formats, from single to 8 digit PIN Codes, including: - 6 and 8 Bits Wiegand, Nibble and Parity bit options, optional Rosslare Format - 1-5 keys, fixed 4 keys and 6 keys BCD with facility code, Wiegand 26 bits - 3x4 Matrix single key - 1 to 8 keys BCD, Clock & Data |
| • Audio/Visual: | Two tri-color LED indicators, Built-in sounder |
| • Design: | Epoxy potted, fully sealed in a rugged metal enclosure, highly strong construction, metallic keys. Suitable for extremely harsh environments. |
| ENVIRONMENTAL CHARACTERISTICS | |
| • Operating Environment: | Water resistant, suitable for outdoor use (IP65) |
| • Operating Temperature: | -31 °C to 63 °C (-25 °F to 145 °F) |
| • Operating Humidity: | 0 to 95% (non-condensing) |
| • RFI Protection: | > 20 V/m up to 1000 MHz |
| PHYSICAL CHARACTERISTICS | |
| • Dimensions: | 120mm x 76mm x 22mm (4.72" x 3" x 0.866") |
| • Weight: | 410g (0.9 lbs) |

System Components

The AY-Q54 is compatible with a variety of Rosslare's access controllers (AC-215, AC-115, AC-020, AC-015), as well as with many third party access control systems.



Additional Information

The AY-Q54 is covered by Rosslare's 5-year Limited Product Warranty.

For sales information or product documentation, please visit our website:
<http://www.rosslaresecurity.com>.

